

Scratched Concrete



Construction	High Performance Luxury Vinyl Tile
Wear/Layer Thickness	0.022" (0.55 mm)
Overall Thickness	0.098" (2.5mm)
Tile Size	24" x 36"
Class/ASTM F1700	Class III Printed film vinyl plank, Type B (Embossed)
Backing Class	Commercial grade
Finish	UV Cured Polyurethane
Edge Profile	Straight
Incorporated Antimicrobial	Yes
Installation	Glue Down
Recommended adhesive	Beaulieu LVT Adhesive
Square Feet Per Carton	48 ft
Pieces Per Carton	8
Weight Per Carton	44 lbs
Cartons Per Pallet	40

Performance

Critical Radiant Flux	ASTM 648-10
Smoke Density	ASTM E 662
Slip Resistance	ASTM D 2047
Flexibility	ASTM F137
Residual Indentation	ASTM 1914-07
Resistance to heat	ASTM F 1514-04
Resistance to Chemicals	ASTM F 925-02
Dimensional Stability	ASTM F 2199-09
Recycled Content	up to 20% by weight (pre-consumer)
10 Year Limited Commercial Warranty	



Charcoal 001



Grey 002

All designs are ©Beaulieu Group, LLC All Rights Reserved

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.

201 Princeton Blvd.
PO Box 1110
Adairsville, GA 30103
(800) 451-1250

335 Roxton Street
Acton Vale, Quebec
Canada J0H1AQ
(888) 467-5075

